
MADRAX DIVISION



GRABER MANUFACTURING, INC. 1080 UNIEK DRIVE WAUNAKEE, WI 53597 P(800) 448-7931, P(608) 849-1080, F(608) 849-1081 WWW.MADRAX.COM, E-MAIL: SALES@MADRAX.COM



30" Allows for Tire Clearance to Wall

## Circa and Genesis Rack Installation Guide CHECK LOCAL CODES

Installation Guide Applies to The Following Madrax Bike Racks: • Circa Bike Rack

- Genesis Bike Rack

CONFIDENTIAL DRAWING AND INFORMATION IS NOT TO BE COPIED OR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF GRABER MANUFACTURING, INC. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

©2017 GRABER MANUFACTURING, INC. ALL PROPRIETARY RIGHTS RESERVED.

There must be at least a six foot clear walkway from buildings to comply with the American with Disabilities Act. The bicycle rack cannot be located directly in front of a store entrance or exit, nor in a driveway. The bicycle rack cannot be located closer to the curb than two feet. Three feet from curb is ideal, although in certain circumstances, the distance may be greater.

The footprint of a bicycle is approximately 2 feet by 6 feet. Some handlebars can be as much as 30 inches wide.

## NOTES:

- 1.
- INSTALL BIKE RACKS ACCORDING TO MANUFACTURER'S SPECIFICATIONS. CONSULTANT TO SELECT COLOR (FINISH), SEE MANUFACTURER'S SPECIFICATIONS. SEE SITE PLAN FOR LOCATION OR CONSULT OWNER.
- 2. 3.